

HARDOX® 450 PLATE

2018-01-12

The table shows available dimensions in mm for direct order including the maximum length.

- Some restrictions, contact your local sales representative for more information
- Some restrictions on dimensions and minimum quantities, contact your sales representative for more information.
- Outside the range of dimensions
- Only 1650 mm width, mill edges -0/+70 mm. Other dimensions must be approved by product manager Haradox®. For thermally cut edges, contact local sales force

Minimum length: 2000 mm
 Minimum quantities:
 Thickness: 3.0-60.0
 60.1-100.0
 100.1-120.0
 120.1-
 Min. position weight:
 2.5 tons
 3.5 tons
 4.0 tons
 5.0 tons

| Width | 1000- | 1351- | 1501- | 1650 | 1601- | 1701- | 1801- | 1901- | 2001- | 2101- | 2201- | 2301- | 2401- | 2501- | 2601- | 2701- | 2801- | 2901- | 3001- | 3101- | 3201- | 3301- | 3350 | |
|---------------|-------|-------|-------|------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|------|-------|
| Thickness | 1350 | 1500 | 1600 | | 1700 | 1800 | 1900 | 2000 | 2100 | 2200 | 2300 | 2400 | 2500 | 2600 | 2700 | 2800 | 2900 | 3000 | 3100 | 3200 | 3300 | | | |
| 3.2 - 3.9 | | | | | | | | | | | | | | | | | | | | | | | | |
| 4.0 - 4.7 | | | | | | | | | | | | | | | | | | | | | | | | |
| 4.8 - 5.7 | | | | | | | | | | | | | | | | | | | | | | | | |
| 5.8 - 6.0 | | | | | | | | | | | | | | | | | | | | | | | | |
| 6.1 - 6.7 | | | | | | | | | | | | | | | | | | | | | | | | |
| 6.8 - 7.7 | | | | | | | | | | | | | | | | | | | | | | | | |
| 7.8 - 8.7 | | | | | | | | | | | | | | | | | | | | | | | | |
| 8.8 - 10.0 | | | | | | | | | | | | | | | | | | | | | | | | |
| 10.1 - 25.0 | | | | | | | | | | | | | | | | | | | | | | | | |
| 25.1 - 26.0 | | | | | | | | | | | | | | | | | | | | | | | | 14600 |
| 26.1 - 27.0 | | | | | | | | | | | | | | | | | | | | | | | | 14200 |
| 27.1 - 28.0 | | | | | | | | | | | | | | | | | | | | | | | | 14000 |
| 28.1 - 29.0 | | | | | | | | | | | | | | | | | | | | | | | | 14200 |
| 29.1 - 30.0 | | | | | | | | | | | | | | | | | | | | | | | | 14100 |
| 30.1 - 31.0 | | | | | | | | | | | | | | | | | | | | | | | | 13700 |
| 31.1 - 32.0 | | | | | | | | | | | | | | | | | | | | | | | | 13300 |
| 32.1 - 33.0 | | | | | | | | | | | | | | | | | | | | | | | | 13100 |
| 33.1 - 34.0 | | | | | | | | | | | | | | | | | | | | | | | | 12600 |
| 34.1 - 35.0 | | | | | | | | | | | | | | | | | | | | | | | | 12200 |
| 35.1 - 36.0 | | | | | | | | | | | | | | | | | | | | | | | | 11800 |
| 36.1 - 37.0 | | | | | | | | | | | | | | | | | | | | | | | | 11400 |
| 37.1 - 38.0 | | | | | | | | | | | | | | | | | | | | | | | | 11000 |
| 38.1 - 39.0 | | | | | | | | | | | | | | | | | | | | | | | | 10600 |
| 39.1 - 40.0 | | | | | | | | | | | | | | | | | | | | | | | | 10200 |
| 40.1 - 45.0 | | | | | | | | | | | | | | | | | | | | | | | | 10000 |
| 45.1 - 50.0 | | | | | | | | | | | | | | | | | | | | | | | | 9700 |
| 50.1 - 55.0 | | | | | | | | | | | | | | | | | | | | | | | | 9500 |
| 55.1 - 60.0 | | | | | | | | | | | | | | | | | | | | | | | | 9000 |
| 60.1 - 65.0 | | | | | | | | | | | | | | | | | | | | | | | | 8400 |
| 65.1 - 70.0 | | | | | | | | | | | | | | | | | | | | | | | | 8000 |
| 70.1 - 75.0 | | | | | | | | | | | | | | | | | | | | | | | | 7600 |
| 75.1 - 80.0 | | | | | | | | | | | | | | | | | | | | | | | | 7200 |
| 80.1 - 85.0 | | | | | | | | | | | | | | | | | | | | | | | | 6800 |
| 85.1 - 90.0 | | | | | | | | | | | | | | | | | | | | | | | | 6400 |
| 90.1 - 95.0 | | | | | | | | | | | | | | | | | | | | | | | | 6000 |
| 95.1 - 100.0 | | | | | | | | | | | | | | | | | | | | | | | | 5800 |
| 100.1 - 105.0 | | | | | | | | | | | | | | | | | | | | | | | | 5400 |
| 105.1 - 110.0 | | | | | | | | | | | | | | | | | | | | | | | | 5100 |
| 110.1 - 115.0 | | | | | | | | | | | | | | | | | | | | | | | | 4900 |
| 115.1 - 120.0 | | | | | | | | | | | | | | | | | | | | | | | | 4700 |
| 120.1 - 125.0 | | | | | | | | | | | | | | | | | | | | | | | | 4400 |
| 125.1 - 130.0 | | | | | | | | | | | | | | | | | | | | | | | | 4200 |

HARDOX® 450 SHEET

The table shows available dimensions in mm for direct order including the maximum length. Cut lengths with mill edges, black

- Some restrictions, please contact product manager or Tech support, techsupport@ssab.com
- Outside the range of dimensions

Min. length 1500mm
 Min. bundle weight 2 ton

| Width | 950- | 1001- | 1201- | 1251- | 1301- | 1501- | 1526- | 1551- | 1601- |
|-------------|------|-------|-------|-------|-------|-------|-------|-------|-------|
| Thickness | 1000 | 1200 | 1250 | 1300 | 1500 | 1525 | 1550 | 1600 | 1650 |
| 2.00 - 2.49 | | | | | | | | | |
| 2.50 - 2.99 | | | | | | | | | |
| 3.00 - 3.19 | | | | | | | | | |
| 3.20 - 3.99 | | | | | | | | | |
| 4.00 - 4.49 | | | | | | | | | |
| 4.50 - 4.79 | | | | | | | | | |
| 4.80 - 4.99 | | | | | | | | | |
| 5.00 - 5.99 | | | | | | | | | |
| 6.00 - 6.40 | | | | | | | | | |
| 6.41 - 6.50 | | | | | | | | | |
| 6.51 - 6.99 | | | | | | | | | |
| 7.00 - 8.00 | | | | | | | | | |
| 7.00 - 8.00 | | | | | | | | | |
| 8.10 - 10.0 | | | | | | | | | |
| 10.1 - 25.0 | | | | | | | | | |
| 25.1 - 26.0 | | | | | | | | | |
| 26.1 - 27.0 | | | | | | | | | |

Min position weight is one coil (17 kg/width-mm) cut into cut to length sheets of the same thickness and width. Delivery weight accuracy +/- 10 %, at least -2 tons / +3 tons.

HARDOX® Cold Rolled SHEET

The table shows available dimensions for direct order including the maximum length (mm)

- Preferred length 1000 - 8000 mm
- Outside the range of dimension

| Width | 800 | 1001- | 1251- | >1500 |
|-------------|------|-------|-------|-------|
| Thickness | 1000 | 1250 | 1500 | |
| 0.70 - 0.90 | | | | |
| 1.00 - 1.39 | | | | |
| 1.40 - 1.99 | | | | |
| 2.00 - 2.10 | | | | |
| > 2.10 | | | | |