

HARDOX® 500 PLATE

2018-01-12

HARDOX® 500 SHEET

The table shows available dimensions in mm for direct order including the maximum length

- Some restrictions, contact your local sales representative for information
- Outside the range of dimensions
- Only 1650 mm width, mill edges -0/+70 mm. Other dimensions must be approved by product manager Hardox®. For thermally cut edges, contact local sales force

Minimum length: 2000 mm
 Minimum quantities:
 Thickness: Min. position weight:
 3.0-60.0 2.5 tons
 60.1-100.0 3.5 tons
 100.1-120.0 4.0 tons
 120.1- 5.0 tons

The table shows available dimensions in mm for direct order including maximum length
 Cut lengths with mill edges, black

- Some restrictions, please contact product manager or Tech support, techsupport@ssab.com
 - Outside the range of dimensions
- Min. length 1500 mm
 Min. bundle weight 2 ton

Width	1000-	1351-	1501-	1601-	1650	1701-	1801-	1901-	2001-	2101-	2201-	2301-	2401-	2501-	2601-	2701-	2801-	2901-	3001-	3101-	3201-	3301-		
Thickness	1350	1500	1600	1700		1800	1900	2000	2100	2200	2300	2400	2500	2600	2700	2800	2900	3000	3100	3200	3300	3350		
3.0- 3.7																								
3.8- 4.7																								
4.8- 5.7																								
5.8- 6.7																								
6.8- 7.7																								
7.8- 8.7																								
8.8- 10.0																								
10.1- 24.0																								
24.1- 25.0																								
25.1- 26.0																							14400	
26.1- 27.0	14000																					14200	13800	
27.1- 28.0	13400																					14200	13700	13300
28.1- 29.0	13000																					14100	13700	12900
29.1- 30.0	12500																					14100	13600	12800
30.1- 31.0	12100																					14100	13600	12800
31.1- 32.0	11800																					14200	13700	12800
32.1- 33.0	11400																					14200	13700	12800
33.1- 34.0	11100																					14400	13800	13300
34.1- 35.0	10700																					13900	13400	12900
35.1- 36.0	10400																					14100	13600	13100
36.1- 37.0	10200																					14300	13700	13200
37.1- 38.0	9900																					13900	13400	12900
38.1- 39.0	9600																					14200	13600	13000
39.1- 40.0	9400																					13800	13200	12700
40.1- 45.0	8300																					14400	13800	13200
45.1- 50.0	7500	13500	13500	13500		13500	13400	12700	12100	11500	11000	10600	10100	9700	9400	9000	8700	8400	8200	7900	7700	7600	7600	
50.1- 55.0	6800	11200	11200	11200		11200	11200	11200	11000	10500	10000	9600	9200	8900	8500	8200	7900	7700	7400	7200	7000	6900	6900	
55.1- 60.0	7800	11200	11200	11200		11200	11100	10600	10100	9600	9200	8800	8400	8100	7800	7500	7300	7000	6800	6600	6400	6300	6300	
60.1- 65.0	7200	11200	11200	11200		10800	10300	9700	9300	8900	8500	8100	7800	7500	7200	6900	6700	6500	6300					
65.1- 70.0	6700	10800	10800	10700	12100	10100	9500	9000	8600	8200	7900	7500	7200	6900	6700	6400	6200							
70.1- 75.0	6200	10100	10100	10000	11300	9400	8900	8400	8000	7700	7300	7000	6700	6500	6200									
75.1- 80.0	5900	9400	9400	9400	10600	8800	8300	7900	7500	7200	6900	6600	6300											
80.1- 100.0	8400	8400	7900	7500	8500	7100	6700	6400	6100	5800														
100.1- 103.0	8400	8400	7900	7100	8000	7100	6700	6400	6100	5800														
103.1- 115.0																								
115.1- 130.0																								
130.1- 150.0																								

Width	950-	1001-	1201-	1251-	1301-	1501-	1526-	1551-	1576-	1601-	1626-
Thickness	1000	1200	1250	1300	1500	1525	1550	1575	1600	1625	1650
2.00- 2.49											
2.50- 2.99											
3.00- 3.09											
3.10- 3.19											
3.20- 3.99											
4.00- 4.49											
4.50- 4.79											
4.80- 4.99											
5.00- 5.99											
6.00- 6.40											
6.41- 6.50											
6.51- 7.00											
7.10- 8.00											
8.10- 10.0											
10.1- 25.0											
25.1- 26.0											
26.1- 27.0											

Min position weight is one coil (17 kg/width-mm) cut into cut to length sheets of the same thickness and width.
 Delivery weight accuracy +/- 10 %, at least -2 tons / +3 tons.

